

Techline 16

	Inlet Pressure(m)	Dripper spacing (m)				
		0.30	0.33	0.40	0.50	1.00
1.6 l/h	20	105	114	136	165	291
	30	125	136	162	196	348
	40	140	153	181	220	392
2.3 l/h	20	83	90	107	130	230
	30	98	107	127	155	275
	40	110	120	143	174	309
3.5 l/h	20	63	68	81	99	176
	30	75	81	96	118	210
	40	84	91	108	132	236

Techline 17

	Inlet Pressure(m)	Dripper spacing (m)				
		0.30	0.33	0.40	0.50	1.00
1.6 l/h	20	128	139	164	198	343
	30	153	166	196	236	410
	40	171	186	220	265	462
2.3 l/h	20	90	109	129	156	271
	30	120	131	154	186	325
	40	135	147	173	209	365
3.5 l/h	20	77	83	98	119	207
	30	91	99	117	142	247
	40	102	111	132	159	278

Minimum Pressure-5 (m)

* For maximal length at other inlet pressure, please consult your Netafim contact
* Other spacings can be supplied on request

Ordering guide

Description	Flow rate (l/h)	Spacing (m)	Color	Wall Thickness (mm)	Coil Length (m)
Techline 16	1.6	0.30	Brown	1.0	500*
	2.3	0.33	Dark Brown	1.2	400**
		0.40			100
	3.5	0.50			50
		1.00			25

Example: Techline 16: 2.3 l/h 0.40m Dark brown 1.2mm 50m

Description	Flow rate (l/h)	Spacing (m)	Color	Wall Thickness (mm)	Coil Length (m)
Techline 17	1.6	0.30	Brown	1.0	500*
	2.3	0.33	Dark Brown	1.2	400**
		0.40			100
	3.5	0.50			50
		1.00			25

Example: Techline 17: 3.5 l/h 0.50m Brown 1.0mm 100m

* 1.0 mm Wall Thickness only ** 1.2 mm Wall Thickness only

Connectors

Start connectors




Insert female thread



Stabilizer



Insert male thread



Dripper plug



Insert connectors



Line end



*Available for Techline 17 only

Distributed by:

E-mail: postmaster@netafim.com *Website: www.netafim.com

TECHLINE[®] 16&17mm



- ### Applications
- Sub-surface and on-surface installations
 - Steep slopes and rolling terrain
 - Turf, shrubs, trees
 - Robust and Durable for long lasting installations



Pressure compensating mode



Initiation of flushing cycle



Flushing cycle



Pressure compensating mode

- ### Specification Features & Advantages
- Accurate pressure compensated mechanism for 100% uniformity up to 400 m laterals
 - Patented turbulent flow path
 - Continuous self flushing mechanism
 - Over 20 years of global field proven performance
 - UV resistant
 - Dripper flow rates: 1.6, 2.3, or 3.5 l/h
 - Pressure compensating range: 0.5-4.0 bar (0.5-3.5 bar for 1.0 mm wall thickness)
 - Recommended filtration: 120 mesh
 - Techline 16: O.D.-16, I.D 13.6 or 14.0
 - Techline 17: O.D.-17, I.D 14.6 or 15.0



NETAFIM
LANDSCAPE DIVISION