

SUNNYFLO

QUALITY BRAIDED LAYFLAT HOSE

This braided layflat hose is ideal for lighter duty applications in Industrial, Irrigation and Mining industries.

SUNNYFLO BLUE

Construction: Braided Polyester Yarns plus PVC cover and inner lining extruded for maximum bonding

Working Temperature: - 21°C to 76 °C

| Internal Diameter (mm) | Max. Working Pressure (kPa) | Max. Burst Pressure (kPa) | Wall Thickness (mm) | Standard COIL (m) |
|------------------------|-----------------------------|---------------------------|---------------------|-------------------|
| 38mm | 550 kPa | 1700 kPa | 1.50 mm | 100 m |
| 50mm | 550 kPa | 1700 kPa | 1.50 mm | 100 m |
| 76mm | 550 kPa | 1600 kPa | 1.60 mm | 100 m |
| 102mm | 480 kPa | 1400 kPa | 1.70 mm | 100 m |
| 152mm | 410 kPa | 1350 kPa | 1.90 mm | 100 m |

SUNNYFLO RED

Construction: Thicker Braided Polyester Yarns plus PVC cover and inner lining extruded for maximum bonding

Working Temperature: - 21°C to 76 °C

| Internal Diameter (mm) | Max. Working Pressure (kPa) | Max. Burst Pressure (kPa) | Wall Thickness (mm) | Standard COIL (m) |
|------------------------|-----------------------------|---------------------------|---------------------|-------------------|
| 38mm | 1000 kPa | 3100 kPa | 2.00 mm | 100 m |
| 50mm | 1000 kPa | 3100 kPa | 2.20 mm | 100 m |
| 76mm | 1000 kPa | 3100 kPa | 2.41 mm | 100 m |
| 102mm | 1000 kPa | 3100 kPa | 2.59 mm | 100 m |
| 152mm | 1000 kPa | 3100 kPa | 3.02 mm | 100 m |

For heavy duty applications refer to Crusader Hose range.