

FILTERS & SCREENS

• DRINKING WATER TREATMENT FILTERS

PURETEC WATER FILTERS come with 36 month warranty on drinking water systems & housings (cartridges excluded). Specialty cartridges and housings are available on request.

DISCOUNT CODE: 2.0

Part No.	DESCRIPTION	Flow Rate	
AX12	White Standard Filter Housing 10" , ¾" BSPF connection, No spanner required (Easy Seal), Applications include: <ul style="list-style-type: none"> • Drinking water systems • Whole house filtration • Food service, Commercial, Industrial, Agricultural • Liquid Filtration Pressure rated to 900 KPa at 52°C	up to 76 l/min	View Product
AX12B	<u>Units supplied complete with mounting Bracket</u> Bracket Only		Contact Us

PURETEC CARTRIDGES TO SUIT AX12 MODEL 10" HOUSING

Rust & Sediment Filter Cartridges			
WD011	10", 1 micron, std. diameter, spiral wound rust & sediment cartridge, cyst removal	26	View Products
WD011-C	10", 1 micron, std. diameter, spiral wound rust & sediment cartridge, colloidal removal (negatively charged)	5	
WD051	10", 5 micron, std. diameter, spiral wound rust & sediment	27	
WD101	10", 10 micron, std. diameter, spiral wound rust & sediment	32	
WD201	10", 20 micron, std. diameter, spiral wound rust & sediment	38	
WD251-H	10", 25 micron, std. diameter, spiral wound rust & sediment, Hot water application	39	
View Products			
PL011-A	10", 1 micron, Pleated std. diameter, reusable, cyst removal	38	View Products
PL051-C	10", 5 micron, Pleated std. diameter, cellulose	43	
PL101-C	10", 10 micron, Pleated std. diameter, cellulose	44	
PL201-C	10", 20 micron, Pleated std. diameter, cellulose	45	
PL201	10", 20 micron, Pleated std. diameter, recleanable	45	
PL501	10", 50 micron, Pleated std. diameter, recleanable	48	

Taste, Odour & Heavy Metal Removal Filter Cartridges (Std. Diameter)			
IC051	10", 5 micron, impregnated carbon taste & odour cartridge (ex T01-5) Suitable up to 52°C	19	View Products
GC051	10", 5 micron, granular carbon post filter high taste & odour reduction	13	
GC201-R	10", 20 micron, granular carbon, resin media, post filter high taste & odour reduction	15	
DP101	10" Carbon Dual Purpose Std., Low Press. High Flow, suitable up to 66°C (used on gravity feed rainwater tanks)	25	
CE941	10" Ceramic cart., Taste, Odour, Sediment, Bacterial & heavy metal removal, 0.4 micron	7	View Products
CB101	10", 10 micron carbon block cartridge, Suitable up to 85°C	18	
CB051	10", 5 micron carbon block cartridge, Suitable up to 85°C	16	
CB951-H	10", 0.5 micron carbon block, cyst/ heavy metal removal	15	

Scale Control Filter Cartridges (Std. Diameter)			
SC051	10", Triple action 5 micron, protects appliances, food service equipment & water coolers	16	Contact Us

- **INLINE FILTERS & STRAINERS**

ARAG 'IN-LINE' POLYPROPYLENE WATER IRRIGATION FILTERS c/w SCREEN & BACK FLUSH TAP					
Maximum operating temperature: 60°C				DISCOUNT CODE: 2.0	
Code	Size – BSPM	Max. Flow rate (100 Mesh) L/min @ 60 PSI	Max Working Pressure (PSI)		
Model 32 – Threaded Housing					
ARAG20	¾"	115	170	View Products	
ARAG25	1"	165	142		
ARAG32	1¼"	195	142		
ARAG40	1½"	220	142		
ARAG50	2"	220	115		
Model 33 – Threaded Nut Housing					
ARAG50CH	2" (32,50,80 & 100 Mesh)	300	115		
ARAG80CH	3" (32,50,80 & 100 Mesh)	800	115		
ARAG50CH	2" (120 & 150 Mesh)	300	115		
ARAG80CH	3" (120 & 150 Mesh)	800	115		

1" Unit also available with 120 Mesh Disc Cartridge		
1" Unit Discs only (120 Mesh)		
Flush tap ¾" Male (for 1½" & 2" filter units)		
Flush tap ¾" Female (for ¾" & 1" filter units)		
Body 'O' Ring Suit 1½" / 2" Unit		

ARAG SCREEN DATA				
MESH SIZE	OLD COLOUR	NEW COLOUR	MESH MATERIAL	OPENING SIZE
32	White	Red	S/Steel	0.45mm
50	Blue	Blue	S/Steel	0.30mm
80	Grey	Yellow	S/Steel	0.20mm
100	Red	Green	S/Steel	0.17mm
120	Green	Grey	Plastic	0.13mm
150	Orange	Orange	Plastic	0.09mm

¾" & 1" ARAG Inline filter



1¼" ARAG Inline filter



1½" & 2" ARAG Inline filter



ARAG FILTER SCREENS ONLY			
SIZE	MESH RANGE		
¾" Threaded	32, 50, 80		
	100, 120, 150		
1" Threaded	32, 50		
	80, 100, 120, 150		
1¼" Threaded	32, 50, 80		
	100, 120, 150		
1½" & 2" Threaded	32, 50, 80		
	100, 120, 150		
2" Clamped Housing	32, 50, 80, 100		
	120, 150		
3" Clamped Housing	32, 50, 80, 100		
	120, 150		

ARAG Inline filter screens



Y STRAINERS BRASS TESTED & WATERMARKED
 0.4mm Triangular 304 S/Stl. 1600kPA

CODE	BSPF Thread size		
YSC15	1/2"	View Products	
YSC20	3/4"		
YSC25	1"		
YSC32	1 1/4"		
YSC40	1 1/2"		
YSC50	2"		
YSC65	2 1/2" **		
YSC80	3" **		
YSC100	4" **		



** Note: 2 1/2", 3" & 4" are not tested and watermarked.

Y STRAINERS 316 S/STEEL

CODE	SIZE		
YSST15	1/2"	View Products	
YSST20	3/4"		
YSST25	1"		
YSST32	1 1/4"		
YSST40	1 1/2"		
YSST50	2"		



POLYPROPYLENE HOSE TAIL STRAINERS

CODE	HOSE SIZE		
PPS32	1 1/4"	View Products	
PPS40	1 1/2"		
PPS50	2"		
PPS76	3"		



CARBON STEEL STRAINERS

CODE	BSPF THREAD SIZE		
GIS40	1 1/2"	View Products	
GIS50	2"		
GIS63	2 1/2"		
GIS76	3"		
GIS102	4"		



- **STAINLESS STEEL WEDGEWIRE SUCTION SCREEN & SPEARS**

LOWERING SPEARS			
			
Code	Item Description		
SSLS125	1¼" Stainless Steel BSP LOWERING SPEAR with blanked off Stainless Steel Disc & fitted with 1¼" BSP Female (45mm OD), 600mm Length, Flow Rate: 400 Gal./hr	View Products	
SSLS200	2" Stainless Steel BSP LOWERING SPEAR with blanked off Stainless Steel Disc & fitted with 2" BSP Female (63mm OD), 600mm Length, Flow Rate: 600 Gal./hr		
DRIVE SPEARS			
			
SSDS125	1¼" Stainless Steel DRIVE SPEAR with Hard Black NYLON DRIVE POINT & 1½" Male or Female BSP thread. Low carbon mild steel base, 45mmOD, 600mm length, Flow rate: 400 Gal./hr	View Products	
SSDS200	2" Stainless Steel DRIVE SPEAR with Hard Black NYLON DRIVE POINT & 2" Male BSP thread. Low carbon mild steel base, 56mmOD, 600mm length, Flow rate: 600 Gal./hr		

Notes:

1. Standard screens are made from AISI 304 S/St.
2. Standard slot size is No.6 (6 Thou / 0.15mm) Other slot sizes are available on request
3. No. 10 (10 Thou / 0.25mm) slot size recommended for Creek/River Beds
4. No. 4 (No.4 is 0.10mm slot size) slot size recommended for coastal / Island use (fine sand).
5. Lengths indicated are effective wedge wire screen lengths
6. All prices are Ex Brisbane Store & subject to change without prior notice
7. Stainless Steel pipe fittings also available in pipe fittings section.
8. OTHER SCREEN LENGTHS AVAILABLE FOR HIGHER FLOW RATES P.O.A.
9. **Made to order/ customized suction screens & spears with non-standard slot sizes and product dimensions will not be subject to credit return policy**

STANDARD SUCTION SCREEN			
Code	Item Description		
SSS50	200mm length, 113mm ID x 123mm OD, 1mm Slot Size, 2" BSPF Thread, 2289 Gal./hr	View Product	

Longer sizes or larger diameters also available for higher flow rates P.O.A.



