

WATER METERS

BETA-SDC Multi- Jet Dry Dial Turbine Water Meter

Horizontal installation only

CODE	SIZE	Nom. Flow Rate (m ³ /hr)	Max. Flow Rate (m ³ /hr)	Min. Flow Rate (L/hr)	Unit Weight (Kg)		
B/SDC-15	1/2"MI	1.5	3	30	1.5	View Products	
B/SDC-20	3/4"MI	2.5	5	50	1.7		
B/SDC-25	1"MI	3.5	7	70	2.6		
B/SDC-32	1 1/4"MI	6	12	120	2.8		
B/SDC-40	1 1/2"MI	10	20	200	5.1		
B/SDC-50	2"FI	15	30	300	8.5		

FEATURES INCLUDE:

- Suitable for industrial, commercial & irrigation markets
- Technically advanced pulse output which provides for more measurement accuracy
- Standard setting: 1 pulse per Litre (1/2" to 1 1/2" units) and 1 pulse per 10 L (2" unit)
- Fusion Bonded Epoxy coated body
- Hermetically vacuum sealed register
- Maximum reading: 99999 m³
- Magnetic drive
- Meets or exceeds ISO 4064 Class B standard
- **(DRD7111) Digital Re-settable display**
- Available as hot and cold versions: Cold Version up to 50°C
Hot version up to 90°C
- Maximum operating water pressure: 16 Barg



OMEGA WOLTMAN Water Meter

Horizontal installation only

CODE	SIZE	Nom. Flow Rate (m ³ /hr)	Max. Flow Rate (m ³ /hr)	Min. Flow Rate (m ³ /hr)	Unit Weight (Kg)		
OMEGA50	2"	15	30	0.75	14	View Products	
OMEGA65	2 1/2"	25	50	0.75	13		
OMEGA80	3"	40	80	1.2	16		
OMEGA100	4"	60	120	1.8	18		
OMEGA150	6"	150	300	4.5	42		
OMEGA200	8"	250	500	7.5	64		
OMEGA250	10"	400	800	12	94		
OMEGA300	12"	600	1200	18	114		

FEATURES INCLUDE:

- Suitable for industrial, commercial & irrigation markets
- High quality fusion bonded epoxy coated body
- Hermetically vacuum sealed register
- Magnetic drive transmission allows register to keep completely dry
- Meets or exceeds ISO 4064 Class B standard
- **(DRD7111) Digital Re-settable display @ \$121.00 ea + GST Less Disc.: 2.5**
- Available with reed switch pulse output
- Low pressure head loss even at high flow rates
- Flanges according to AS2129
- Pulse settings: 2"- 4" size: 100 Litres/ pulse
6"-8" size: 1000 Litres/ pulse
10" – 12" size: 10000 Litres/ pulse
- Available as hot and cold versions: Cold Version up to 50°C
Hot version up to 90°C
- Maximum operating water pressure: 16 Bar
- Larger sizes available

