MONSOON &

Monsoon Hurricane HC

Hard Hose Irrigator

Standard Equipment Fitted

- Hydraulic Telescopic Front Jack on Draw Bar
- · Completely Hot Dipped Galvanised
- PTO Rewind Shaft
- Tractor Feed Hydraulic System
- Hydraulic Rear Stabiliser Legs
- Hydraulic Slew/Rotation of Reel
- Automatic Trolley Lift System

- Pressure Gauge
- · Layflat Delivery Hose 6M with take of coupling to suit
- PTO Winding Handle
- 4 Speed Gearbox
- Direct Coupled Turbine
- · Safety Cut Out System for Hose Indexing
- Rewind Speed Controller (Includes hose counter & Irrigation run timer)
- Solar Panel & 12v Battery

Hose Size Options

- 125mm / 430m 460m
- 125mm / 520m 540m

Optional Extras

- Slow Closing Valve
- Controller Pressure Gauge
- Controller 3 Multi Speed Upgrade
- Purge Kit
- Dual Wheel

Sprinkler Gun Model

- Komet Ultra 160 Sprinkler Gun
- Fully Galvanised
- 3 Wheel Trolley with Counter Weights



MODEL	INLET PRESSURE REQUIRED	FLOW RATE	UNIFORM WATERED AREA
125/420	5.2 - 7.0 BAR	12.5 - 25.6	72 - 78
125/460	5.0 - 7.3 BAR	14.8 - 24	66 - 78



Monsoon Hurricane HC Performance Chart

Model 125-520with Sprinkler Gun

PEH	HOSE: O.D.	. mm		FIELD-PIE	PE LENGT	н	мт	SPE	EED I/H		EED T/H		EED T/H		EED T/H		EED I/H		EED I/H		EED T/H		EED T/H
125		520				- 1	0	20		30		4	40		50		60		70		80		
nozzle diam mm	nozzle pres bar	mt	Flow mc/h	Flow I/min	Flow I/s	Pull to pull dist. mt	Irrigated area per pull Ha	rate mm	inlet pres bar														
26	2	30.78	35.9	599	10	49.3	2.56	73	2.9	36	3.0	24	3.2	18	3.4	15	3.5	12	3.7	10	3.9	9	4.0
26	3.0	37.70	44.0	733	12.2	60.3	3.14	73	4.2	36	4.4	24	4.5	18	4.7	15	4.9	12	5.0	10	5.2	9	5.4
26	4	43.54	50.8	847	14.1	69.7	3.62	73	5.5	36	5.7	24	5.9	18	6.0	15	6.2	12	6.4	10	6.5	9	6.7
26 26	5 6	48.67 53.32	56.8 62.2	947 1037	15.8 17.3	77.9 85.3	4.05 4.44	73 73	6.8 8.1	36 36	7.0 8.3	24	7.2 8.5	18 18	7.3 8.6	15 15	7.5 8.8	12	7.7 9.0	10	7.8 9.1	9	9.3
28	2	31.95	41.7	695	11.6	51.1	2.66	82	3.1	41	3.3	27	3.4	20	3.6	16	3.8 5.2	14	3.9	12	4.1	10	4.3 5.7
28 28	3.0	39.13 45.18	51.0 58.9	851 982	14.2 16.4	62.6 72.3	3.26 3.76	82 82	4.5 6.0	41	4.7 6.1	27	4.9 6.3	20	5.0 6.5	16 16	6.6	14	5.4 6.8	12	5.5 7.0	10	7.1
28	5	50.51	65.9	1098	18.3	80.8	4.20	82	7.4	41	7.5	27	7.7	20	7.9	16	8.0	14	8.2	12	8.4	10	8.5
28	6	55.33	72.2	1203	20.0	88.5	4.60	82	8.8	41	8.9	27	9.1	20	9.3	16	9.4	14	9.6	12	9.8	10	9.9
30	3	40.50	58.6	977	16.3	64.8	3.37	90	4.9	45	5.1	30	5.3	23	5.4	18	5.6	15	5.8	13	5.9	11	6.1
30	4.0	46.77	67.7	1128	18.8	74.8	3.89	90	6.5	45	6.6	30	6.8	23	7.0	18	7.1	15	7.3	13	7.5	11	7.6
30	5	52.29	75.6	1261	21.0	83.7	4.35	90	8.0	45	8.2	30	8.3	23	8.5	18	8.7	15	8.8	13	9.0	11	9.2
30	6	57.28	82.9	1381	23.0	91.6	4.77	90	9.5	45	9.7	30	9.9	23	10.0	18	10.2	15	10.4	13	10.5	11	10.7
30	7	61.86	89.5	1492	24.9	99.0	5.15	90	11.0	45	11.2	30	11.4	23	11.5	18	11.7	15	11.9	13	12.0	11	12.2
32	3	41.83	66.7	1111	18.5	66.9	3.48	100	5.4	50	5.6	33	5.7	25	5.9	20	6.1	17	6.2	14	6.4	12	6.6
32	4.0	48.30	77.0	1283	21.4	77.3	4.02	100	7.1	50	7.3	33	7.4	25	7.6	20	7.8	17	7.9	14	8.1	12	8.3
32	5	54.00 59.15	86.1	1434	23.9	86.4	4.49	100	8.8	50 50	8.9	33	9.1	25	9.3	20	9.4	17	9.6	14	9.8	12	9.9
32 32	6 7	63.89	94.3	1571 1697	26.2	94.6 102.2	4.92 5.32	100	10.4	50	10.6 12.3	33	10.8 12.4	25 25	10.9 12.6	20	11.1	17	11.3 12.9	14	11.4	12	11.6
34 34	3	43.12 49.79	75.3 86.9	1254 1448	20.9	69.0 79.7	3.59 4.14	109 109	6.0 7.8	55 55	6.1 8.0	36 36	6.3 8.2	27	6.5 8.3	22	6.6 8.5	18	6.8 8.7	16 16	7.0 8.8	14	7.1 9.0
34	5	55.66	97.2	1619	27.0	89.1	4.14	109	9.7	55	9.9	36	10.0	27	10.2	22	10.4	18	10.5	16	10.7	14	10.9
34	6	60.97	106.4	1774	29.6	97.6	5.07	109	11.5	55	11.7	36	11.8	27	12.0	22	12.2	18	12.3	16	12.5	14	12.7
34	7	65.86	115.0	1916	31.9	105.4	5.48	109	13.3	55	13.5	36	13.7	27	13.8	22	14.0	18	14.2	16	14.3	14	14.5
36	4	51.23	97.4	1624	27.1	82.0	4.26	119	8.7	59	8.9	40	9.0	30	9.2	24	9.4	20	9.5	17	9.7	15	9.9
36	5	57.28	108.9	1815	30.3	91.6	4.77	119	10.8	_	10.9	40	11.1	30	11.3	24	11.4	20	11.6	17	11.8	15	11.9